



STCS

SMALL TRANSIT
CASE COMPUTER
SYSTEM

CP Technologies STCS are small form factor modules that provide powerful Xeon processing performance optimized for virtualization applications, gigabit switching and routing capabilities and over 10 minutes of sustained battery backup time. All modules are ROHS compliant and made with high-strength 5052-H32 aircraft-grade aluminum. CP STCS are optimized for low size, weight and power (SWaP) to meet the demand of portability, reliability, and performance from any customer. These systems accommodate flexible mounting options with brackets that can be mounted in a standalone configuration, to a bulkhead, in a half rack/case, or a standard 19" rack. In a sealed system configuration, these STCS are designed for harsh environments.

CHASSIS SPECS

MODULE DIMENSIONS

Server 3.45"H x 9.125"W x 11.25"D
Switch 3.45"H x 10.20"W x 10.125"D
Router 1.74"H x 9.125"W x 11.25"D
UPS 3.45H x 11.25D x 9.125w x 11.25D
Transit Case 22.25"H x 15.66"W x 24"D

WEIGHT

Server/UPS unit - 10 lbs (4.5 kg)
Switch/Router unit - 12 lbs (5.4 kg)

CONSTRUCTION

Sheet/Milled Aluminum
ROHS Compliant
Clear Chem Film and Black Powder Coating
IP65 Compliant Sealing
Conduction Cooled



Who We Are

CP Systems designs, fabricates and integrates standard and customized high-performance computing platforms and LCD monitors for military, industry, and commercial applications.

Using COTS components, CP Systems provides solutions for customers who need reliable systems that will operate in a variety of harsh conditions and who require revision control and hardware consistency for multi-year programs.

CP Systems is an ITAR Registered and ISO 9001:2015 Certified business that has been operating for over twenty years.

Assembled in the USA
ISO 9001:2015 Certified
ITAR Registered

CP Systems
2620 Deep Well Ranch Rd
Prescott, AZ 86301
CP-Systems.Tech
858.571.4330



TECH SPECS

SERVER MODULE

CPU	Intel® Xeon® D Family Processor, 4-16 Core CPU available
MEMORY	Up to 512GB DDR4 2400 MT/s ECC
GRAPHICS	1 x VGA
NETWORKING	2 LAN with 10GBase-T
STORAGE	Up to 4x Removable SATA SSD
OPERATING SYSTEM	Windows Server, VMware
SPECIAL FEATURES	Serial RS232, Hardware RAID Controller (RAID 0, 1, 5), software sanitization of drives (Zeroize)
FRONT PANEL IO	20-33VDC in, IPMI LAN, 2x USB (3.0), 2 Ethernet ports, Up to 4x Drive bays, Video port

SWITCH MODULE

SYSTEM BOARD	Embedded Cisco Catalyst 3560-CX <ul style="list-style-type: none"> • 8x 10/100/1000 GE ports • 2x 1GE copper uplinks • 2x 1GE SFP uplinks • IP base (IP services with RTU license)
SYSTEM MEMORY	128 MB on-board flash memory, 512 GB DRAM
FRONT I/O CONNECTIONS	20-33VDC in, (8x) 10/100/1000 GE ports (12 ports optional), (2x) GE uplink, (2x) 10GB SFP uplink (optional), USB

ROUTER MODULE

FEATURES	Onboard hardware encryption processor supporting IP Security (IPsec) Secure Sockets Layer with transparent LAN services (SSL/TLS) Secure Real-time Transport Protocol (SRTP) Triple Digital Encryption Standard (3DES) Advanced Encryption Standard (AES) Internet Key Exchange (IKE)
SYSTEM BOARD	Embedded Cisco ESR 5915 <ul style="list-style-type: none"> • 5x 10/100 ports • 2x routed • 3x switched • 1x RS-232 Console port
SYSTEM MEMORY	256 MB on-board flash memory, 512 GB DRAM
FRONT I/O CONNECTIONS	20-33VDC in, (5x) 10/100/1000 GE ports (12 ports optional), (2x) GE uplink, (2x) 10GB SFP uplink (optional), USB

UPS MODULE

FEATURES	300 Watt UPS Lithium Iron Phosphate battery with >10 min Hold Time @ 80% Universal AC Input of 96-132VAC and from 47-63 Hz Over Voltage Capacity for Managed In-Rush and Startup Demands Over Voltage and Over Temperature Protection Circuits Common Safety Ground Connection Integrated Battery Switch for long term storage protection
FRONT I/O CONNECTIONS	1X 110-240 VAC in, 3x 10-33 VDC out, Status and Indicator LEDs

QUESTIONS?

Reach out to us at
CP-Systems.Tech
or call 858.571.4330

ENGINEERED TO YOUR SPECIFICATIONS

- In-house engineering department
- Design and build of rapid prototypes. Experience with solving difficult customer application problems through knowledge of the industry and custom system design and manufacturing capability
- Our Engineers use Solid Works 3D CAD modeling software for mechanical design and thermal simulation
- Design experience with MIL-STD-167, MIL-STD-461, MIL-STD-810, and MIL-DTL-901, in addition to FCC, UL, CE, and country specific agency requirements

FACILITY AND TEST

- All integration work is performed in a state-of-the-art, ESD-controlled facility
- Our facility has 23,000 sqft and has dedicated 12,000 sqft to manufacturing and 3,000 sqft to engineering
- Operate to anti-static standard ANSI/ESD S20.20-2007 and electronics assembly standard IPC-A-610, Revision E-2010

REVISION CONTROL & CONFIGURATION MANAGEMENT

- Our Program Managers will assure your products are revision controlled for the life of the program
- Configuration Management to assure TAA Compliance and system compatibility
- One part number for life of the program
- Counterfeit and obsolescence management

QUALITY COUNTS

- ISO 9001:2015 Certified
- 100% system inspection before shipment
- All integrated systems undergo a minimum 24-hour system test and burn-in before shipment to the customer
- Assistance with 3rd party verification of system specifications
- 5-year warranty on all servers and 3-year warranty on LCD monitor products
- TAA compliant
- Built in the USA